

Electronic Pressure Catalog > Submersible Liquid Level > LS-10

Type LS-10 Submersible Liquid Level Transmitter 100 InWC to 100 psi

Standard Features

- **Signal output:** 4-20 mA 2-wire
- **Supply voltage:** 10-30 VDC
- **Process connection:** G1/2B with removable protective cap
- **Electrical connection:** Vented polyurethane cable (must specify length)




Important Ordering Instructions: Specify the **level transmitter part number** and **cable length part number** corresponding to the total required cable length. For example, a 100 InWC level transmitter with 40 feet of cable should be ordered as 4262761 / 4347931.

Pressure range part number AND cable length part number must be specified on every order!

Cable Length Part Numbers

CABLE LENGTH SELECTOR					
Length	Part#	Length	Part #	Length	Part #
5 feet	4347868	60 feet	4347974	130 feet	4348075
10 feet	4347876	65 feet	4347982	140 feet	4348083
15 feet	4347885	70 feet	4347990	150 feet	4348091
20 feet	4347893	75 feet	4348006	160 feet	4348105
25 feet	4347906	80 feet	4348016	170 feet	4348113
30 feet	4347915	85 feet	4348024	180 feet	4348121
35 feet	4347923	90 feet	4348032	190 feet	4348139
40 feet	4347931	95 feet	4360903	200 feet	4348147
45 feet	4347949	100 feet	4348040	250 feet	4364479
50 feet	4347957	110 feet	4348058	300 feet	4366340
55 feet	4347966	120 feet	4348066	Contact factory for lengths over 300 feet	



LS-10 Standard Ranges

Gauge Ranges	
Description	
Range	Part #
0-100 InWC	4262761
0-150 InWC	4262779
0-250 InWC	4262787
0-400 InWC	4262795
0-5 psi	4262809
0-10 psi	4262817
0-15 psi	4262825
0-25 psi	4262833
0-30 psi	4262841
0-50 psi	4262850
0-100 psi	4262868

NOTE: Ready-to-ship part numbers shown in **bold, blue** print.

Ready-to-ship part numbers are available from stock (subject to prior sale). Items without part numbers are available on special order.



NOTE: LS-10 "Ready-to-Ship" submersible transmitters require assembly from factory stocked components and usually ship in three days or less.